## PanoramaXX Maxximize your horizon.

## TECHNICAL DATA

Description	Fully automated welding mask with extra-large field of vision: the nose cut- out floats above the nose to position the auto-darkening filter closer to the weld- er's eyes. True-Color filter protects at shade levels 2.5/5-12M with Autopilot (automatic shade selection), +/- 2 in- dividual shade-preference adjustment, sensitivity control and opening delay with optional twilight function.	EN379 classification	Optical class: 1
			Scattered light: 1
			Homogeneity: 1
			Angular dependence: 2
		Shape stability	Welding mask: up to 220 °C / 428 °F
			Front cover lens: up to 137 °C / 279 °F
		Eye protection	Ultraviolet / Infrared Protection: maximum protection at any shade level
Shade levels	inactive: shade level 2,5 active, manual: shade level 7-12 Automatic protection level regulation across a range from 5-12 with individual calibration option of ± 2	Operating temperature	-10°C to + 70°C / 14°F to 158°F
Autopilot		Storage temperature	-20°C to + 80°C / -4°F to 176°F
		Weight	550 g / 19,4 oz
Power supply	Solar cells, lithium-polymer battery, rechargeable by USB-cable	Application ranges	ication ranges Any electric arc welding process Electrode Welding (Stick Welding, SMAW) / MIG / MAG (GMAW) / GMAW High melting rate process / Flux Cored Wire Welding / TIG welding (GTAW) / Plasma Arc Welding / Plasmacutting & Oxy-gas
Battery life	300 to 500 charging cycles		
Sensors	Five Sensors		
Sensitivity	Infinitely adjustable, now with "super high" sensitivity		Welding / Grinding in Grind Mode
			Prohibited for laser welding!
Switching time	bright to dark: 0.090 ms at room temperature 0.070 ms at 55°C	Scope of delivery	Welding helmet, manual, storage bag, Micro USB cable, warranty card and one front cover lens
	dark to bright: 0.1 s to 2.0 s (with twilight function)	Standards	CE, ANSI Z87.1 (ADF and helmet shell), EAC, complies with CSA Z94.3
Field of vision	Depending on headband setting, 2.3x to 6.3x field of vision of a 100 x 50 mm standard industry ADF	Warranty	2 years 1 year warranty extension (except batte- ries) for online product registration within the first 6 months.
			http://register.optrel.com

http://register.optrel.com



optrel AG industriestrasse 2 CH-9630 wattwil switzerland www.optrel.com info@optrel.com